



Features

- Intel ATOM D2550 1.86 GHz
- 12.1" TFT 1280 x 800 wide-screen, 400 cd/m², 50,000 hours
- DC 12~24V
- Aluminum front bezel and painted steel chassis, fan-less design
- Panel or VESA mount, IP65 front bezel
- Suitable for industrial applications

Specifications

CPU Type	ATOM D2550 1.86 GHz
Chipset	Intel NM10
Memory	2G
I/O Interface	2 x USB 2.0 RS232, COM1 RS232/422/485, COM2 RS232/422/485, COM3 2 x GbE RJ-45 1 x DVI-I
Display	12.1" TFT-LCD, 1280 x 800 Luminance 400 (cd/m ²) View angle 176/176 (H°/V°) Backlight Lifetime 50,000 hours Contrast ratio 1000:1
Touch Screen	5-wire resistive touch
Power	12~24V DC, 35W
Construction	Aluminum front bezel and painted steel chassis
Net Weight(Kgs)	
Mounting	Panel Mount, VESA 100 x 100
Dimensions	319.0 (W) x 225.0 (H) x 56.8 (D) mm
Operating Temp.	0°C ~ 50°C
Storage Temp.	-20° ~ 80°C
Humidity	10% ~ 90% @ 40°C (non-condensing)
Certification	EN 61000-6-4, EN 61000-6-2

Ordering Information

A12W

12.1" TFT 1280 x 800 fan-less HMI with D2550 1.86 GHz CPU, 2G memory, resistive touch screen, 12~24V DC input, aluminum front bezel and painted steel chassis, IP65 front bezel.

