

Extreme High-Pressure Gauges and Transducers

**PRESSURE RANGES FROM
0-20,000 PSIG THROUGH 0-145,000 PSIG**



402 / 502 Series



400 / 500 Series



615 Series



740 / 760 Series

Extreme High-Pressure Gauges and Transducers

When the pressure's on, count on NOSHOK



Applications:

- Water Jet Cutting
- Hydroforming
- Burst Testing
- High Pressure Filtration
- High Pressure / High Torque Tools
- High Pressure Lubrication
- High Pressure Pumping



400 / 500 Series Extreme High Pressure Gauges

- 4" and 6" Case Sizes in Standard Dry or Liquid-filled Configurations
- SS Case and Socket, Open Front Design with Blowout Protection on the Rear of the Case
- Pressure Ranges from 0-20,000 psig through 0-60,000 psig
- Standard 9/16" - 18 UNF 3B High Pressure Process Connection
- Standard Accuracy of +/- 1% Full Scale
- Available with Most Standard Options and Accessories



740 / 760 Series Extreme High Pressure Gauges

- 4 1/2" Phenolic Turret, Safety Case in Standard Dry or Liquid-filled Configurations
- Solid Front, Safety Case, Blow-out Back Design
- Pressure Ranges from 0-20,000 psig through 0-60,000 psig
- Standard 9/16" - 18 UNF 3B High Pressure Process Connection
- Standard Accuracy of +/- 1% Full Scale
- Available with Most Standard Options and Accessories



402 / 502 Series Extreme High Pressure Gauges

- 6" Solid Front, Safety Case in Standard Dry or Liquid-filled Configurations
- Solid Front, Safety Case, Blow-out Back Design
- Pressure Ranges from 0-80,000 psig through 0-100,000 psig
- Standard 9/16" - 18 UNF 3B High Pressure Process Connection
- Standard Accuracy of +/- 1% Full Scale
- Available with Most Standard Options and Accessories



615 Series Extreme High Pressure Transducers

- 4-20A Current or Voltage Outputs (0-10 vdc, 0-5 vdc, etc.)
- Pressure Ranges from 0-20,000 psig through 0-145,000 psig
- Standard 9/16" - 18 UNF 3B High Pressure Process Connection
- Standard Accuracy of +/- 0.25% (BSFL)
- Full Compliment of Optional Electrical Connectors

For more detailed information, contact your local NOSHOK distributor or NOSHOK direct.

Corporate Headquarters

1010 West Bagley Road
Berea, Ohio 44017
Ph: 440.243.0888
Fax: 440.243.3472
E-mail: noshok@noshok.com
Web: www.noshok.com

The
Instrumentation
Company

NOSHOK
INCORPORATED