



Features

- Intel® ATOM™ N2600 1.6 GHz Dual Core Processor
- 12.1" TFT, 800x600 (4:3), 330 cd/m², 50,000 hours
- DC 9~36V
- Aluminum chassis, fan-less design
- Panel or VESA mount, IP65 front bezel.
- Suitable for industrial applications

Specifications

CPU Type	Intel® ATOM™ Cedar View N2600 1.6 GHz Dual Core Processor
Chipset	Intel® NM10
Memory	2GB
Graphics	Intel® NM10 Build-in
I/O Interface	2 x USB 2.0 Type A, USB 4/5 RS232/422/485, COM1, Default RS-232 RS232, COM2 1 x Line out phone jack 2 x GbE RJ-45
Expansion	1 x Mini PCI-E (Half-size)
Display	12.1" TFT-LCD, 800 x 600 Luminance 330 (cd/m ²) View angle 160/140 (H°/V°) Backlight Lifetime 50,000 hours Contrast Ratio 800:1
Touch Screen	5-wire resistive touch
Power	DC 9~36V
Construction	Sliver aluminum front bezel and chassis
Net Weight(Kgs)	4.0 Kg
Mounting	Panel Mount, VESA 100x100
Dimensions	319.0 (W) x 245.0 (H) x 52.0 (D) mm
Operating Temp.	0°C~ 50°C
Storage Temp.	-20°C ~ 60°C
Humidity	10% to 90% @ 40°C, (non-condensing)
Certification	CE/FCC Class A

Ordering Information

PP-A12

12.1" TFT 800x600, fan-less HMI with ATOM N2600 1.6 GHz CPU Dual Core, 2GB memory, resistive touch screen, 9~36V DC input, silver aluminum front bezel and chassis, IP65 front bezel.

