Nylon Coiled Hose

reelin-Wade's Nylon coiled tubing is tough and abrasion resistant. The hoses are fitted with durable brass male swivel compression fittings and spring guards that are preassembled on each hose end. Bulk hoses are offered in 100 foot lengths for users wanting to assemble their own hoses.

Our Nylon Twin Hose (pictured below) has all of the same features but with the added benefit of two hoses bonded together. An intermittent bond allows for easy fitting installation and eliminates taping or tie wrapping hoses together in twin line applications. One line is yellow and the second is a natural translucent color which allows for visual flow verification. Contact Customer Service for more information.

The difference between the Self-Storing Hose and the Mini Coils is that the Self-Storing Hose includes fittings.



Features

- Economical and lightweight.
- Self retracting.
- Resists oil, grease and corrosion.
- Pre-sealed threads on swivel fittings.

Specifications

Temperature Range -60°F to +180°F

Vacuum Rating
To 28" Hg.

Diameter Tolerances ±.004"



Resin Compliance Meets UL94HB Testing Requirements



Nylon Self-Storing Hose

| Part Number & Color Code | OD | ID | Working 75°F/25°C | Pressure 150°F/65°C | Material Length | Working Length | Retracted Length | Coil OD | MPT Fitting | Approx. Weight |
|-----------------------------|-----------|------|----------------------|------------------------|--------------------|-------------------|---------------------|---------|-------------|-------------------|
| N14-12B | .309" | 1/4" | 185 PSI | 110 PSI | 12' | 9' | 5-1/4" | 3-1/2" | 1/4" | .375 lbs. |
| N14-25B | | | | | 25' | 19' | 10" | | 1/4" | .62 lbs. |
| N14-50B | | | | | 50' | 37.5' | 19-3/4" | | 1/4" | .937 lbs. |
| N14-100 | | | | | 100' | 75' | 39-1/2" | | none | 1.37 lbs. |
| N38-12B | .470" | 3/8" | 165 PSI | 100 PSI | 12' | 9' | 4-1/2" | 5-5/8" | 3/8" | .687 lbs |
| N38-25B | | | | | 25' | 19' | 9" | | 3/8" | 1.62 lbs. |
| N38-50B | | | | | 50' | 37.5' | 18-1/4" | | 3/8" | 1.75 lbs. |
| N38-100 | | | | | 100' | 75' | 36-3/4" | | none | 4 lbs. |
| N12-12B | .625" | 1/2" | 170 PSI | 110 PSI | 12' | 9' | 4-1/4" | 9" | 1/2" | .375 lbs. |
| N12-25B | | | | | 25' | 19' | 8-1/2" | | 1/2" | .562 lbs. |
| N12-50B | | | | | 50' | 37.5' | 15-1/2" | | 1/2" | .937 lbs. |
| N12-100 | | | | | 100' | 75' | 31-1/2" | | none | 1.37 lbs |
| Variation A | vailable: | | | | | | | | Po | ackaging |

Resource Guide-Chemical Resistance Chart

his information was provided to Freelin-Wade by our suppliers and other sources. It is to be used only as a general reference guide to aid in the selection of products in which chemical and material compatibility issues are a factor. This guide is not intended as a complete nor conclusive database. Freelin-Wade does not guarantee these ratings since the resistance of a material can be greatly affected by the temperature, consistency, and presence of other chemicals. Ultimately, the consumer must determine the chemical compatibility of an item based on the conditions in which the product is being used.

| | PUR | PE | PVC | Nylon | Kynar |
|--|-------------|---------------|----------------|-------|-------|
| Acetic Acid, Glacial Acetic Acid, 30% | 4 | 2 | 4 | 2 | 1 |
| Acetone | 4 | 2 | 4 | 1 | 4 |
| Acetylene Alkazene | 4 | • | 1 | 1 | - |
| Aluminum Chloride (aq) Aluminum Nitrate (aq) | 3 | 2 | 1 2 | | 1 |
| Ammonia Anhydrous | 4 | 2 | 1 | i | 4 |
| Ammonia Gas (cold) Ammonia Gas (hot) Ammonium Chloride (aq) 40% | 4 | | - | 1 | 4 |
| Ammonium Chloride (aq) 40% Ammonium Sulfate (aq) | 2 | 1 | 1 | 1 | 1 |
| Amyl Alcohol Amyl Naphthalene | 4 | 2 | 1 | | 1 |
| Animal Fats | 1 | - | - | | - |
| Aqua Regia Arsenic Acid | 3 | 2 | 3 | | 1 |
| Asphalt ASTM Fuel A | 2 | 1 | 1 | | 1 |
| ASTM Fuel B | 3 | - | . 4 | | - |
| ASTM Fuel C Barium Chloride (aq) | 3 1 | 1 | 1 | 1 | 1 |
| Beer Beet Sugar Liquors | 2 | 2 | 1 | 1 | 1 |
| Benzene | 3 | 4 | 3 | 1 | 1 |
| Benzine Blast Furnace Gas | 2 | - | - | - | |
| Bleach Solutions Borax | 4 | 1 | 1 | | 1 |
| Boric Acid | 1 | 1 | i | - | 1 |
| Brake Fluid Brine | 2 | • | 3 | • | 1 |
| Bromine Water | 4 2 | - | 3 | 4 | 1 |
| Bunker Oil Butane | 1 | 3 | 3 | 1 | 1 |
| Butter Butyl Alcohol (Butanol) | 3 | 1 | 3 | 1 | 1 |
| Butylene Calcium Chloride (aq) | 4 | 1 | 1 | i | 1 |
| Calcium Hydroxide (aq) | 2 | i | 2 | | 1 |
| Calcium Nitrate (aq) Calcium Sulfide (aq) | 1 | - | 1 | 1 | 1 |
| Cane Sugar Liquors | 4 | - 4 | 1 | - | 1 |
| Carbolic Acid Carbon Dioxide | 1 | 2 | 1 | - | 1 |
| Carbonic Acid Carbon Monoxide | 4 | 2 | 1 | - | 1 |
| Carbon Tetrachloride Castor Oil | 4 | 4 | 4 | 3 | 1 |
| Chlorine (dry) Chlorine (wet) | 4 | 3 | 4 | 4 | 1 |
| Chlorine (wet) Chloroform | 4 | 3 | 4 | 3 | 1 |
| Chlorox | 4 | ī | 4 | 4 | 1 |
| Chromic Acid 50% | 1 | i | 2 | 1 | 1 |
| Coal Tar (Creosote) Coconut Oil | 3 | i . | 1 | - | 1 |
| | 1 | 1 | 1 | | - |
| Copper Chloride (aq) | 1 | 2 | 1 | | 1 |
| Coke Oven Gas Copper Chloride (aq) Copper Cyanide (aq) Corn Oil | 1 | 2 | 1 2 | | 1 |
| Coffon Seed Oil | 1 | 1 | 2 | 4 | 1 |
| Creosol (Methyl Phenol) Cychlohexane | 1 | 4 | 4 | 1 | i |
| Denatured Alcohol Detergent Solution | 3 | 1 | 1 | | |
| Diesel Oil | 2 | 3 | 1 | | 4 |
| Dioxane Dowtherm Oil | 3 | - | - | - : | - |
| Dry Cleaning Fluids Ethane | 4 | - | 1 | - | - |
| Ethyl Acrylate | 4 | - 2 | - 3 | 3 | 1 |
| Ethyl Alcohol (Ethanol) Ethyl Benzine | 4 | - | - | - | - |
| Ethyl Cellulose Ethyl Chloride | 2 | 4 | 4 | | 1 |
| Ethyl Ether | 3 | 4 | 4 | - | 1 |
| Ethylene Chloride Ethylene Glycol ⁵ (Anti-Freeze) | 4 | 4 1 | 4 1 | 1 | 1 |
| Ethylene Oxide Ethylene Trichloride Ferric Chloride (aq) Ferric Sulfate (aq) Ferric Sulfate (aq) | 4 | 3 | 3 | 1 | 1 |
| Ferric Chloride (aq) | 1 | 2 | 1 | | 1 |
| Ferric Sulfate (aq) | 1 2 | - 1 | 1 | | 1 |
| Fluroine (Liquid) Formaldehyde (RT) | 4 | 3 | 4 | 1 | 1 |
| Formic Acid Freon 11 | 4 | 2 | į | 4 | 1 |
| Freon 12 | 4 1 | 3 1 | 1 | 1 | - |
| Freon 22 Fuel Oil (Bunker 'C') | 4 2 | 3 | 1 | 1 | 1 |
| Gasoline (100 Octane, High Test) | 3 | 4 | 3 | 1 | 1 |
| Glue Glycerin (Glycerol) | 1 | 1 | 3 | 1 | 1 |
| Glycerin (Glycerol) Glycols Green Sulfate Liquor | 4 | - | - | 1 - | - |
| Hexane | 2 | 41 | 2 ² | - | ī |
| Hydraulic Oil Hydrochloric Acid (cold) 37% | 1 | 1-3 2 | 1 2 | 4 | 1 |
| Hydrochloric Acid (hot) 37% | 4 | - | - | 4 | 1 |
| Hydrofluroic Acid (Conc.) (cold) Hydrofluroic Acid (Conc.) (hot) | 4 | 2 | - | • | 1 |
| Hydrogen Gas Isobutyl Alcohol | 3 | 1 | 1 - | 1 | 1 |
| Isooctane | 3 2 4 | 3 | 1 | | 1 |
| Isopropyl Acetate Isopropyl Alcohol (Isopropanol) | 3 | 1 | - | 1 | 1 |
| Isopropyl Ether Kerosene | 2 1 | 1 4 | 2 | 1 | 1 |
| | · | | _ | · | |

| | PUR | PE | PVC | Nylon | Kynar |
|---|------------------|------------------|--------|--------|--------|
| Lacquers Lacquer Solvents | 4 | 1 | 4 | | |
| Lard | 1 | i | i | | 1 |
| Lavender Oil Lead Acetate (aq) | 4 | 1 | 1 | | 1 |
| Linseed Oil Liquified Petroleum Gas | 2 | 3 | 1 | 1 | 1 |
| Lubricating Oils | 1-2 ³ | 4 | 2 | 1 | 1 |
| Lye Magnesium Chloride (aq) | 4 | 1-4 ⁴ | 1-2 | 1 | 1 |
| Magnesium Hydroxide (aq) | 4 | 2 | 1 | - | 1 |
| Mercury Methane | 3 | 1 | 1 2 | 1 | 1 |
| Methyl Acetate | 4 | 2 | 4 | 1 | 1 |
| Methyl Acrylate Methyl Alcohol (Methanol) | 4 | 1 | 1 | i | i |
| Methyl Butyl Ketone Methyl Chloride | 4 | 4 | 1 | 1 | 1 |
| Methylene Chloride Methyl Ethyl Ketone | 4 | 4 | 4 | - | 1 |
| Methyl Ethyl Ketone Methyl Isobutyl Ketone | 4 | 2 | 4 | 1 | 4 |
| Milk | 4 | - 1 | - 1 | 1 | 1 |
| Mineral Oil Motor Oil 20W, 10W40 | 1 | 3 | 1 | 1 | 1 |
| Naphtha (Lighter Fluid) | 2 | 4 | 1 | 1 | 1 |
| Naphthalene (Moth Repellent) Natural Gas | 2 | 2 | 4 1 | 1 | 1 |
| Neatsfoot Oil Nitric Acid 70% | 1 | - | - | - 4 | 1 |
| Nitric Acid (Dilute) 10% | 3 | 2 | 1 | 4 | 1 |
| Nitroethane | 4 | i | - | | 1 |
| N-Octane Oleic Acid | 2 | 1 | 3 | 1 | 1 |
| Oleic Acid Oleum Spirits Olive Oil | 3 1 | 4 | 4 | | 4 1 |
| Oxygen (cold) | 1 | - | - | 1 | 1 |
| Oxygen (cold) Oxygen (200-400F) | 4 | | - | | |
| Paint Thinner, Duco Perchloric Acid | 4 | ī | 3 | - | 1 |
| Perchloroethylene | 2 | 3 | 3 | 3 | 1 |
| Petroleum - Below 250F Petroleum - Above 250F | 4 | - | - | 4 | - |
| Phenol (Carbolic Acid) Phenyl Ethyl Ether Phosphoric Acid - 45% | 3 | 2 | 3-4 | 4 | 1 |
| Phosphoric Acid - 45% | 4 | 1 | 2 | 2 | 1 |
| Pickling Solution Picric Acid | 4 | 1 | 4 | 3 | 1 |
| Potassium Acetate (aq) | 4 | - | - | - | 1 |
| Potassium Chloride (aq) Potassium Cyanide (aq) | 1 | 2 | 1 | | 1 |
| Potassium Hydroxide (aq) | 4 | 1 | 1 | 3 | 4 |
| Producer Gas Propane | 1 | 1 | 1 | 1 | 1 |
| Propyl Alcohol (Propanol) | 4 | ī | 1 | - | 1 |
| Propylene Propylene Glycol (Anti-Freeze) | 3 | 1 | 3 | 2 | 1 |
| Propylene Oxide | 4 | 2 | - | - | 4 |
| Pydraul, 10E, 29 ELT Pydraul 30E, 50E, 65E | 4 | | - | | |
| Pydraul, 115E | 4 | - | | - : | |
| Pydraul 230E, 312C, 540C Rapeseed Oil | 2 | 4 | - | - | - |
| RJ-1 (MIL-F-23338 B) RP-1 (MIL-F-25576 C) | 1 | | | | |
| Salt Water | 2 | 1 | 1 | 1 | 1 |
| Sewage Silicate Esters | 1 | - | - | - | 1 |
| Silicone Oils | 1 | 1 | i | • | 1 |
| Silver Nitrate Skydrol 500 | 1 | 1 | 1 | | 1 |
| Skydrol 500 Skydrol 700 | 4 | - | - | - | |
| Soap Solutions Sodium Chloride (aq) | 3 | 4 | 1 | 1 | - |
| Sodium Hydroxide (aq) | 4 | 1 | 1 | 2 | 4 |
| Sodium Peroxide (aq) Sodium Phosphate (aq) | 1 | 1 - | 2 | | 1 |
| Sodium Sulfate (aq) | 1 | 1 | 1 | | - |
| Soy Bean Oil Stoddard Solvent | 2 1 | 3 | 1 | | 1 |
| Styrene (Monomer) | 4 | 2 | 4 | - 1 | 1 |
| Sucrose Solution Sulfuric Acid (Dilute Battery Acid) | 3 | 1 | i | - | i |
| Sulfuric Acid (Conc) Sulfuric Acid (20% Oleum) | 4 | 2 | 4 | | 1 |
| Sulturous Acid | 4 | 2 | 1 | - : | - |
| Tannic Acid Tetrochlorethylene | 4 | 1 2 | 1 | | 1 |
| Toluene (Toluol) | 4 | 3 | 4 | 1 | 1 |
| Transformer Oil Transmission Fluid Type A | 2 | | 2 | - | |
| Trichloroethane | 4 | 4 | 3 | 3 | 1 |
| Trichloroethylene Turbine Oil | 4 1 | 3 | 4 | 3 1 | 1 |
| Turpentine | 4 | 4 | 4 | 1 | 1 |
| Varnish Vinegar | 3 | 3 | 4 | 1 | 1 |
| Vinyl Chloride | 4 | 4 | 4 | - | 1 |
| Water Whiskey, Wines | 1 2 | 1 | 1 | 1 | 1 |
| White Oil | 1 | - | - | - | - |
| Wood Oil Xylene | 3 4 | 4 | 4 | 1 | 1 |
| Zinc Acetate (aq) | 4 | - | | | i |
| Zinc Chloride (aq) | 2 | 1 | T | | 1 |
| 1 Petroleum Base 2 Synthetic | Base = | 1. Petr | oleum | Base : | = 3 |

Rating Scale

- 1= Little or no impact
- 2= Minor effect
- 3= Moderate effect
- 4= Severe effect

1 Petroleum Base **2** Synthetic Base = 1, Petroleum Base = 3 **3** SAE 10, 20, 30, 40, 50 = 1, Petroeum = 2

4 Calcium Hydroxide & Potassium (Hydroxide=1, Sodium Hydroxide=4) 5 See Propylene Glycol 6 See Ethylene Glycol