


## Low Wattage Version

### 4/2 Solenoid to operate/spring return

Internal pilot with locking override\* and cable grip connector\*\*\*



Model	Port Size	Cv In to CY2	Cv CY1 to Exh	Cv In to CY1	Cv CY2 to Exh	Voltages***	Operating Pressure**	Pilot Pressure**	Repair Kit
F1012C-CF	1/4" PTF	1.2	1.6	1.2	1.6	24 VDC 2W	30-150 psig	30-150 psig	53473-05
F1012C-CF1WH	1/4" PTF	1.2	1.6	1.2	1.6	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53473-05
F1013C-CF	3/8" PTF	1.4	1.6	1.4	1.6	24 VDC 2W	30-150 psig	30-150 psig	53473-05
F1013C-CF1WH	3/8" PTF	1.4	1.6	1.4	1.6	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53473-05
F1023C-CF	3/8" PTF	3	4.5	3.1	4.3	24 VDC 2W	30-150 psig	30-150 psig	53474-06
F1023C-CF1WH	3/8" PTF	3	4.5	3.1	4.3	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53474-06
F1024C-CF	1/2" PTF	4	5.4	4.1	5.1	24 VDC 2W	30-150 psig	30-150 psig	53474-06
F1024C-CF1WH	1/2" PTF	4	5.4	4.1	5.1	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53474-06
F1025C-CF	3/4" PTF	4.8	5.8	5	5.4	24 VDC 2W	30-150 psig	30-150 psig	53474-06
F1025C-CF1WH	3/4" PTF	4.8	5.8	5	5.4	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53474-06
F1035C-CF	3/4" PTF	10.3	13.1	11	12.5	24 VDC 2W	30-150 psig	30-150 psig	53475-06
F1035C-CF1WH	3/4" PTF	10.3	13.1	11	12.5	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53475-06
F1036C-CF	1" PTF	11.3	14.3	12.9	13.4	24 VDC 2W	30-150 psig	30-150 psig	53475-06
F1036C-CF1WH	1" PTF	11.3	14.3	12.9	13.4	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53475-06
F1037C-CF	1-1/4" PTF	11.6	14.5	14.3	13.7	24 VDC 2W	30-150 psig	30-150 psig	53475-06
F1037C-CF1WH	1-1/4" PTF	11.6	14.5	14.3	13.7	120 VAC 60 Hz 3.5W	30-150 psig	30-150 psig	53475-06

\* For Non-locking override replace the -CF with a -CZ.

\*\* External pilot service replace the 6 digit "C" with a "H", operating pressure will now go to 0, but a minimum of 30 psig and/or greater than supply pressure, required for external pilot supply.

\*\*\* Additional voltages and connector option refer to below tables.

BSPP threads replace the 2 digit "1" with an "A".

#### Note: Additional connectors add the code from table below to the end of the part number

Connector Description	Connector Code	Order Separately
Cable Grip 0 -240VDC/VAC	standard	54934-01
1/2" conduit 0 -240VDC/VAC	1V3	54934-05
Cable Grip with LED 24 VDC/VAC	1V4	54934-08
Cable Grip with LED 120VAC	1VB	54934-02
6' Molded cable 0-240VDC/VAC	1V5	54934-21

#### Examples:

F1023C-CF1WH with a Cable Grip Connector, change to Cable Grip with LED option, order F1023C-CF1WH1V4

F1037C-CF with a Cable Grip Connector, changed to a 6' molded cable option, order F1037C-CF1V5

#### Note: Additional voltages, add or replace the 1WH in above code with the voltage code from table below in the desired part number

Voltage Description	Voltage Code	Order Separately
12 VDC	1WF	54469-01
24 VDC	standard	54469-02
24V 50/60 Hz	1UD	54469-04
120V 50/60 Hz	1WH	54469-03
220/240V, 50/60 Hz	1WN	54469-08

#### Examples:

F1012C-CF 24 VDC, changed to a 12 VDC option, order F1012C-CF1WF

F1025H-CF1WH 120Vac, change to a 220/240V, 50/60Hz option, order F1025H-CF1WN