




## 3.00" X 3.00" Lite Smooth T-Slotted Profile - Eight Open T-Slots

## 3030-LS Profile

3030-LS is a 3.00" x 3.00" lite fractional 15 series square T-slot profile with eight open T-slots, two on each 3.00" face. The profile is smooth, which makes it resistant to dirt and debris buildup while also being easy to clean. The 3030-LS profile is the light-duty version in the 3030 profile family, is compatible with 15 series fasteners, and has a center cavity that can be pressurized up to 150 psi. The eight open T-slots, strength, and ability to pressurize this profile make it a great choice for automation applications, machine frames and workstations.





	Part No.	Series	Stock Length	Material	Alloy**	Finish	Drop Lock	Moment of Inertia	Surface Area	Yield Strength	Modulus of Elasticity	Weight
I	3030-LS *	15	145", 242"	Alumainum	6105-T5	Clear Anodize	2°	IX = 2.6861"4 IY = 2.6861"4	2.659 in. <sup>2</sup>	35,000 psi	10,200,000 lb / in. <sup>2</sup>	0.2593 lb / in.
ĺ	3030-LS-Black-FB		per inch	Aluminum		Black Anodize						

<sup>\*</sup> The above profiles are sold per inch or stock length.

## Standard Machining Services

Service No.	Series	Service Description	Reference Page		
7030	15	Cut to Length	859		
7050	15	Access Hole	863		
7040	15	Anchor Counterbore	865		
7055	15	Tap Profile End	861		

<sup>\*\*</sup> Or comparable